



## Master-Tube PUR A



antistatic



spiral-free



metal-free

### Product Details

#### Construction / Material

- Type of construction: axially extruded tubing without seams or welds
- Execution of the wall: made of highly abrasion-resistant material
- Specifications of the wall: surface resistance  $R_o < 10^8$  Ohm

#### Properties

- Chemical Properties: good resistance to oil / plasticiser-free / good resistance to fats
- Mechanical Properties: kink-resistant
- Physical Properties: good damping behaviour

#### Operating Temperature

- Temperature Range: -40 to 85 °C

#### Application Areas

- Areas of application: Plant & Mechanical Engineering / Industry

#### Customizing Options

- optional item modification (on request): printable / rolls

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

### Individual consultation

We offer consultation by  
phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

