

Master-Tube TPE F

TPV media tubing based on thermoplastic elastomer, highly flexible, for higher temperatures, food-grade, plasticiser-free, with good mechanical fatigue resistance

food approved | spiral-free | metal-free | very flexible

Product Details

Construction / Material

- Type of construction: axially extruded tubing without seams or welds
- Material of the wall: TPE

Properties

- Chemical Properties: good resistance to chemicals
- Mechanical Properties: good mechanical fatigue resistance under dynamic loads
- Flexibility: very flexible
- Physical Properties: flexible at low temperatures

Operating Temperature

- Temperature Range: -40 to 125 °C

Application Areas

- Areas of application: Plant & Mechanical Engineering, Industry, Food & Pharma

Customizing Options

- optional item modification (on request): printable, rolls

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



Individual consultation

We offer consultation by phone: **+55 11 4151 5100**

Product requests via: **https://www.masterduct.com.br/**

Headquarters for your sales area

Masterduct Brasil Comércio de Dutos LTDA.

Rua dos Estados, 18 - Villa Industrial
06516-310- Santana de Parnaiba-SP
Brazil