



Master-PUR LF Lift MHR A

Article Master No.: 012692

PU Absaug- und Förderschlauch, flexibel, permanent antistatisch



antistatic



microbe
resistant



hydrolysis
resistant



flexible



light



moderately
pressure
resistant

Product Details

Key facts

- Product Advantages: tested suitability for continuous use (see PDF download)

Construction / Material

- Type of construction: film hose with embedded support coil
- Spiral Design: made of steel wire
- Material of the spiral: spring steel
- Execution of the wall: made of pure material, made of specified material, addition of a non-migrating permanent antistatic agent, wall thickness between the spirals approx. 0.7 mm
- Material of the wall: polyether polyurethane

Properties

- Specifications of the product: according to TRGS 727 and ATEX 2014/34 EU
- Chemical Properties: odourless and tasteless, good resistance to chemicals, good UV resistance, good ozone resistance, halogen-free, hydrolysis resistant, microbe-resistant, plasticiser-free
- Mechanical Properties: compressible approx. 1:3
- Flexibility: flexible
- Weight: light
- Pressure Resistance: moderately pressure resistant

- Colour: transparent, partially coloured tube

Operating Temperature

- Temperature Range: -40 to 90 °C
- short-term maximum temperature: peaks to 125 °C

Application Areas

- Areas of application: Conveying, lifting & feeding technology

Article Variants


Extended Article Number	Nominal Size (DN) Individual consultation mm	Outer diameter Individual consultation mm	Bending radius* Individual consultation mm	Weight Individual consultation kg/m	Operating pressure Individual consultation bar	Negative pressure Individual consultation bar	Max. Production length Individual consultation m
012692:80:x	80	88	45	0,77	1,3	0,75	20,00
012692:102:x	102	112	56	1,16	1,25	0,73	20,00
012692:120:x	120	130	65	1,39	1,2	0,71	20,00
012692:140:x	140	150	75	1,56	1,15	0,7	20,00
012692:160:x	160	170	85	2,31	1,1	0,69	20,00
012692:180:x	180	190	95	2,51	0,8	0,61	20,00

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).



Individual consultation

We offer consultation by phone: **+55 11 4151 5100**

Product requests via: <https://www.masterduct.com.br/>

Headquarters for your sales area

Masterduct Brasil Comércio de Dutos LTDA.

Rua dos Estados, 18 - Villa Industrial
06516-310- Santana de Parnaíba-SP
Brazil